

CSL0986A - Electrical Flush Control Unit

CSL0986

Specification

- 1 channel flush control box.
- Adjustable timer between 1 and 6 seconds (1 second = 1 litre water approx.)
- Built in purge control to avoid stagmentation.
- 35 second delay between operation.
- Ideal to work with the electrical syphon flush conversion CSL0985.
- Lockout facility.
- CSL0983A (Tactile Button), CSL0983B (Wave On Button), CSL0983C (Piezo) compatible.

NOTE - requires electrically operated button (CSL0983)



CSL0986A
Flush Syphon Control Unit

CSL0986B - Tap Control Unit

Specification

- 2 channel tap control box.
- Adjustable run time from 6 to 20 seconds.
- Built in purge control to avoid stagmentation.
- Lockout facility to help prevent flooding.
- Works with electrically operated stainless steel recessed hand rinses and washbasins.
- Lockout Facility.
- CSL0983A (Tactile Button), CSL0983B (Wave On Button), CSL0983C (Piezo) compatible, CSL0979 (Solenoid Valve) compatible.

NOTE - requires electrically operated button (CSL0983) and solenoid to complete (CSL0979)



CSL0986B
Tap Control Unit

CSL0986C - Shower Control Unit

Specification

- 2 channel shower control box.
- Adjustable run time from 30 to 180 seconds.
- Built in purge control to avoid stagmentation.
- Ideal to work with our electrically operated showers.
- Lockout facility.



CSL0986C
Shower Control Unit

CSL0986D - Washroom Control System

Specification

- Offers complete washroom control.
- 1 x Flush controller built in (1 to 6 seconds programmable).
- 2 x Tap controller built in (10 to 19 seconds programmable).
- 1 x Shower controller built in (60 to 180 seconds programmable).
- Ideal for use with the Cell Security electronic stainless steel sanitary ware range.
- Built in purge control to avoid stagmentation on each channel.
- Lockout facility on each channel.



CSL0986D
Washroom Control System

Urinal Direct Flushing Kit

CSL0987

Specification

- No cistern is required.
- Flushed when user walks away.
- Upto 80% saving on water costs.
- Extremely reliable, low maintenance.
- Solenoid valve(s) included.
- Water pressure minimum 0.5 Bar.

CSL0987A Pack Includes (1 x Bowl)

- 1 x Control Box.
- 1 x Passive infra-red sensor and surround.
- 1 x Solenoid Valve.
- 1 x 3 metre cable.

CSL0987B Pack Includes (2 x Bowl)

- 1 x Control Box.
- 2 x Passive infra-red sensor and surrounds.
- 2 x Solenoid Valves.
- 2 x 3 metre cable.



CSL0987A
1 Bowl Direct Flushing Kit

CSL0987B
2 Bowl Direct Flushing Kit